

BIG Essentials Specification Sheet

Lensed Lara - 17

Project Name:

Type No:

PRODUCT DESCRIPTION

Surface mounted LED Profile with optical control.
 Manufactured in Australia.
 Customisable to suit any projects requirements.
 3-step McAdam binning and high 98 CRI with 98 R9.
 Natural anodised silver as standard.
 White or black powder coated options available.
 Comes with 1m bare tail standard, option for 250mm connector set.
 PMMA acrylic opal or frosted lens' available with different beam angles.
 Two clips supplied per metre.



LUMINAIRE SPECIFICATION

Width:	21mm
Height:	17mm
IP Rating:	IP20 or IP65
Cutting Increment:	45mm
Max Profile Supply Length:	2.5m
Max Single Feed Strip Length:	6W – 20m 10W – 15m 18W – 10m


TECHNICAL

Life maintenance	L80 / B10 @ 74,000 Hours
Strip Output	6W/m @ 600lm 10W/m @ 1000lm 18W/m @ 1600lm
CRI / CCT	2700K / 3000K / 4000K @ CRI 98
Optics	30° / 60° / 90° 15° Frost / 30° Frost / 60° Frost / 90° Frost Opal / Frosted
Drive current	Remote 24V DC constant voltage
Dimming	Dimming options available to suit: phase DALI 0-10V DMX Casambi

CODE BUILDER

Model	Output	Colour Temp	Optic	Finish	IP
LL17	0600 6W/m @ 600lm	W27 2700K	C30 30° Optic	SLV Silver	20 IP20
	1000 10W/m @ 1000lm	W30 3000K	C60 60° Optic	WHT White	65 IP65
	1600 18W/m @ 1600lm	W40 4000K	C90 90° Optic	BLK Black	
			F15 15° Frosted		
			F30 30° Frosted		
			F60 60° Frosted		
			O Opal frosted		
			F Frosted		

Example LL17-0600-W30-O-SLV-IP20



21mm

17mm



Components supplied as standard.