

Neon Neo – Medium VB Wrap

Project Name:

Type No:

PRODUCT DESCRIPTION

Flexible vertical bend >120mm LED ribbon.

UV, flame, chlorine and salt resistant.

Continuous length up to 20 metres.

Colour temperature ranges from 2400K – 4000K.

Ambient temperature -20.C to 45.C.

Remote 24V constant voltage driver.

Five clips supplied per metre for curves. Channel supplied in metre lengths when straight. Bendable profile also available.



LUMINAIRE SPECIFICATION

Width:	16mm
Height:	15mm
IP Rating:	IP67
Cutting Increment:	White – Standard Output – 50mm
Max Length:	White – High Output – 62.5mm Standard 5W - 20m single feed Standard 10W - 15m single feed High Output - 5m single feed


TECHNICAL

Life maintenance	L70 / B10 up to 50,000 hours
Output	Standard Output - 5W/m @ 320lm 10W/m @ 580lm High Output - 10W/m @ 1050lm
CRI / CCT	2400K 2700K 3000K 4000K @ CRI 90
Optics	Opal diffused
Drive current	Remote 24V DC constant voltage
Dimming	Dimming options available to suit: Non Dim DALI 0-10V DMX Casambi

CODE BUILDER

Model	Colour Temp	Wattage	Power Feed
Neo-M-VB-W	24 2400K	S5 5W/m @ 320lm	1 Bottom connector
	27 2700K	S10 10W/m @ 580lm	2 End connector
	30 3000K	H10 10W/m @ 1050lm	3 Side (Left/Right) connector
	40 4000K		

Example Neo-M-VB-W-27-S5-1



ACCESSORIES: Mounting clip or channel

