

Neon Neo – Small HB

Project Name:

Type No:

PRODUCT DESCRIPTION

Flexible horizontal bend >50mm LED ribbon.

UV, flame, chlorine and salt resistant.


Continuous length up to 15 metres.

Colour temperature ranges from 2400K – 4000K.

Ambient temperature -20°C to 45°C.

Remote 24V constant voltage driver.

Five clips supplied per metre for curves. Channel supplied in metre lengths when straight. Bendable profile also available.



LUMINAIRE SPECIFICATION

Width:	5mm
Height:	10mm
IP Rating:	IP67
Cutting Increment:	50mm
Max Length:	Standard Output 5W - 10m single feed Standard Output 10W - 5m single feed High Output 10W - 15m single feed

TECHNICAL

Life maintenance	L70 / B10 up to 50,000 hours
Output	Standard Output - 5W/m @ 130lm 10W/m @ 210lm High Output - 10W/m @ 310lm
CRI / CCT	2400K 2700K 3000K 4000K @ CRI 90
Optics	Opal diffused
Drive current	Remote 24V DC constant voltage
Dimming	Dimming options available to suit: Non Dim DALI 0-10V DMX Casambi

CODE BUILDER

Model	Colour Temp	Wattage	Power Feed
Neo-S-HB	24 2400K	S5 5W/m @ 130lm	1 Bottom connector
	27 2700K	S10 10W/m @ 210lm	2 Axial connector
	30 3000K	H10 10W/m @ 310lm	3 Side connector
	40 4000K		

Example Neo-S-HB-27-S5-1

ACCESSORIES: Mounting clip or channel

