

# BIG Essentials Specification Sheet

## Square Stark – 13

**Project Name:**

**Type No:**

### PRODUCT DESCRIPTION

- Surface mounted LED Profile.
- Manufactured in Australia.
- Customisable to suit any projects requirements.
- 3-step McAdam binning and high 98 CRI with 98 R9.
- Natural anodised silver as standard.
- White or black powder coated options available.
- Comes with 1m bare tail standard, option for 250mm connector set.
- PMMA acrylic opal or frosted lens' available.
- Two clips supplied per metre.



### LUMINAIRE SPECIFICATION

Width:	13mm
Height:	13mm
IP Rating:	IP20 or IP65
Cutting Increment:	45mm
Max Profile Supply Length:	2.5m
Max Single Feed Strip Length:	6W – 20m 10W – 15m 18W – 10m

### TECHNICAL

Life maintenance	L80 / B10 @ 74,000 Hours
Strip Output	6W/m @ 600lm   10W/m @ 1000lm   18W/m @ 1600lm
CRI / CCT	2700K   3000K   4000K @ CRI 98
Optics	Opal – L.O.R. 65% with dot free finish Frosted – L.O.R. 85% where higher efficiency is required
Drive current	Remote 24V DC constant voltage
Dimming	Dimming options available to suit: phase   DALI   0-10V   DMX   Casambi

### CODE BUILDER

Model	Output	Colour Temp	Optic	Finish	IP
SS15	0600 6W/m @ 600lm	W27 2700K	O Opal	SLV Silver	20 IP20
	1000 10W/m @ 1000lm	W30 3000K	F Frosted	WHT White	65 IP65
	1600 18W/m @ 1600lm	W40 4000K		BLK Black	
Example	SS13-0600-W30-O-SLV-20				

