

BIG Essentials Specification Sheet
Wrap Ripley – 20

Project Name:

Type No:

PRODUCT DESCRIPTION

Surface mounted LED Profile with wrap around diffuser.
 Manufactured in Australia.
 Customisable to suit any projects requirements.
 3-step McAdam binning and high 98 CRI with 98 R9.
 Natural anodised silver as standard.
 White or black powder coated options available.
 Comes with 1m bare tail standard, option for 250mm connector set.
 PMMA acrylic opal or frosted lens' available.



LUMINAIRE SPECIFICATION

| | |
|-------------------------------|------------------------------------|
| Width: | 20mm |
| Height: | 20mm |
| IP Rating: | IP20 or IP65 |
| Cutting Increment: | 45mm |
| Max Profile Supply Length: | 2.5m |
| Max Single Feed Strip Length: | 6W – 20m 10W – 15m 18W – 10m |

TECHNICAL

| | |
|------------------|--|
| Life maintenance | L80 / B10 @ 74,000 Hours |
| Strip Output | 6W/m @ 600lm 10W/m @ 1000lm 18W/m @ 1600lm |
| CRI / CCT | 2700K 3000K 4000K @ CRI 98 |
| Optics | Opal – L.O.R. 65% with dot free finish Frosted – L.O.R. 85% where higher efficiency is required |
| Drive current | Remote 24V DC constant voltage |
| Dimming | Dimming options available to suit: phase DALI 0-10V DMX Casambi |

CODE BUILDER

| Model | Output | Colour Temp | Optic | Finish | IP |
|---------|------------------------|-------------|-----------|------------|---------|
| WR20 | 0600 6W/m @ 600lm | W27 2700K | O Opal | SLV Silver | 20 IP20 |
| | 1000 10W/m @ 1000lm | W30 3000K | F Frosted | WHT White | 65 IP65 |
| | 1600 18W/m @ 1600lm | W40 4000K | | BLK Black | |
| Example | WR20-0600-W30-O-SLV-20 | | | | |

